

Amendments to the Claims:

Claim 1 is cancelled and claims 2 to 10 are amended as set forth hereinafter.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Cancelled).

2. (Currently Amended) ~~The hydro bushing of claim 1, wherein~~
A hydro bushing for radially supporting a motor, the hydro
bushing comprising:

a sleeve-shaped outer body;

5 an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between
said outer body and said support body;

a volume-changeable work chamber disposed between said legs
of said spring body and filled with a low-viscous hydraulic
10 fluid;

said volume-changeable work chamber having a clear distance
between said inner support body and said sleeve-shaped outer
body;

at least one compensating chamber disposed laterally of and
15 directly next to said work chamber;

said compensation chamber and said work chamber having a

common lateral surface therebetween;

20 a transfer channel interconnecting said work chamber and
said compensating chamber and being delimited by said common
lateral surface;

said work chamber having an effective cross-sectional
area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a
cross-sectional area (A_2);

25 said cross-sectional area (A_1), said dynamic swell
stiffness, said length (L) and said cross-sectional area (A_2) all
being so selected that said hydro bushing has a natural or
resonant frequency of approximately 130 Hz;

said transfer channel ~~[[is]]~~ being a first transfer channel;

30 said compensating chamber ~~[[is]]~~ being a first compensating
chamber on one side of said work chamber; ~~chamber and said hydro~~
~~bushing further comprises~~

a second compensating chamber on the other side of said work
chamber;

35 a connecting channel connecting said compensating channels
to each other; and,

a second transfer channel interconnecting said work chamber
and said second compensating chamber.

3. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2,
wherein the ratio of the effective cross-sectional area (A_1) of
said work chamber to the cross-sectional area (A_2) of said
transfer channel lies in a range of 0.1 to 10.

4. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio ($A_1:A_2$) of said cross-sectional areas (A_1 and A_2) is approximately 2.2.

5. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio of said length (L) of said transfer channel to said cross-sectional area (A_2) of said transfer channel lies in a range of 0.1 to 4.0.

6. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the ratio of said length (L) of said transfer channel to said cross-sectional area (A_2) of said transfer channel is approximately 1.5.

7. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein said cross-sectional area (A_1) of said work chamber includes a constriction.

8. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the volume of said work chamber and the volume of said transfer channel define a ratio of 0.1 to 4.0.

9. (Currently Amended) The hydro bushing of ~~claim 1~~ claim 2, wherein the volume ratio of said work chamber and said transfer channel is between 1.0 and 3.0.

10. (Currently Amended) ~~The hydro bushing of claim 1, wherein~~
A hydro bushing for radially supporting a motor, the hydro

bushing comprising:

a sleeve-shaped outer body;

5 an inner support body spaced radially from said outer body;

a spring body having two legs and being disposed between
said outer body and said support body;

a volume-changeable work chamber disposed between said legs
of said spring body and filled with a low-viscous hydraulic
10 fluid;

said volume-changeable work chamber having a clear distance
between said inner support body and said sleeve-shaped outer
body;

at least one compensating chamber disposed laterally of and
15 directly next to said work chamber;

said compensation chamber and said work chamber having a
common lateral surface therebetween;

a transfer channel interconnecting said work chamber and
said compensating chamber and being delimited by said common
20 lateral surface;

said work chamber having an effective cross-sectional
area (A_1) and said spring body having a dynamic swell stiffness;

said transfer channel having a length (L) and a
cross-sectional area (A_2);

25 said cross-sectional area (A_1), said dynamic swell
stiffness, said length (L) and said cross-sectional area (A_2) all
being so selected that said hydro bushing has a natural or
resonant frequency of approximately 130 Hz; and,

one of said legs ~~separates~~ separating said work chamber from
30 said compensation chamber and ~~ends~~ ending in spaced relationship

to said sleeve-shaped outer body so as to define said common lateral surface.